

HDPE 100


PE FITTINGS

POLYETHYLENE
Displays GOOD
CHEMICAL
RESISTANCE MATERIAL
STRENGTH AND RIGIDITY
WITHIN A TEMPERATURE
RANGE OF.
40° C and + 80° C.



PE 100

CROSS TEE

SDR 17 - PN 10


PART #	DIAMETER Ød	L	H	S
0329LCRS0200HP	63	184	60	3.71
0329LCRS0250HP	75	203	65	4.41
0329LCRS0300HP	90	240	75	5.29
0329LCRS0400HP	110	275	85	6.47
0329LCRS0450HP	125	295	85	7.35
0329LCRS0600HP	160	370	105	9.41
0329LCRS0800HP	200	435	110	11.76
0329LCRS0900HP	225	442	110	13.24
0329LCRS1000HP	250	493	120	14.71
0329LCRS1200HP	315	558	120	18.53
0329LCRS1400HP	355	640	140	20.88
0329LCRS1600HP	400	468	140	23.53
0329LCRS1800HP	450	740	140	26.47
0329LCRS2000HP	500	810	150	29.41
0329LCRS2200HP	560	875	150	32.94
0329LCRS2400HP	630	960	160	37.06
0329LCRS2800HP	710	1140	210	41.76
0329LCRS3400HP	800	1280	235	47.06



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS