

HDPE 100


PE FITTINGS



POLYETHYLENE
Displays GOOD
CHEMICAL
RESISTANCE MATERIAL
STRENGTH AND RIGIDITY
WITHIN A TEMPERATURE
RANGE OF.
40° C and + 80° C.

PE 100

END CAP

SDR 17 - PN 10


PART #	DIAMETER Ød	L	H	S
O329LCAP0250HP	75	45	35	4.41
O329LCAP0300HP	90	70	60	5.29
O329LCAP0400HP	110	70	55	6.47
O329LCAP0450HP	125	60	48	7.35
O329LCAP0500HP	140	85	70	8.24
O329LCAP0600HP	160	85	70	9.41
O329LCAP0700HP	180	105	90	10.59
O329LCAP0800HP	200	90	75	11.76
O329LCAP0900HP	225	130	115	13.24
O329LCAP1000HP	250	95	85	14.71
O329LCAP1100HP	280	140	120	16.47
O329LCAP1200HP	315	115	90	18.53
O329LCAP1400HP	355	140	115	20.88
O329LCAP1600HP	400	130	100	23.53
O329LCAP1800HP	450	140	115	26.47
O329LCAP2000HP	500	140	115	29.41
O329LCAP2200HP	560	150	115	32.94
O329LCAP2400HP	630	150	115	37.06
O329LCAP2800HP	710	160	125	41.76
O329LCAP3400HP	800	160	125	47.06
O329LCAP3600HP	900	160	125	52.94
O329LCAP4000HP	1000	160	125	58.82
O329LCAP4800HP	1200	200	155	70.59



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS