

HDPE 100

PE FITTINGS



POLYETHYLENE

Displays **GOOD**

CHEMICAL

RESISTANCE MATERIAL

STRENGTH AND RIGIDITY

WITHIN A TEMPERATURE


RANGE OF.

40° C and + 80° C.

PE 100

ELBOW 90°

SDR 11 - PN 16



PART #	DIAMETER Ød	L	H	S
0329NE900200HP	63	133	65	5.73
0329NE900250HP	75	150	75	6.82
0329NE900300HP	90	176	80	8.18
0329NE900400HP	110	195	75	10.00
0329NE900500HP	125	215	80	11.36
0329NE900600HP	140	225	80	12.73
0329NE900700HP	160	270	90	14.55
0329NE900800HP	180	280	90	16.36
0329NE900900HP	200	305	95	18.18
0329NE901000HP	225	350	110	20.45
0329NE901100HP	250	360	100	22.73
0329NE901200HP	280	395	108	25.45
0329NE901400HP	315	415	100	28.64
0329NE901600HP	355	460	100	32.27
0329NE901800HP	400	525	110	36.36
0329NE902000HP	450	630	160	40.91
0329NE902200HP	500	705	180	45.45
0329NE902400HP	560	780	200	50.91
0329NE902800HP	630	865	220	57.27



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS