


# HDPE 100

## PE FITTINGS

**POLYETHYLENE**  
Displays **GOOD**  
**CHEMICAL**  
**RESISTANCE MATERIAL**  
**STRENGTH AND RIGIDITY**  
WITHIN A TEMPERATURE  
RANGE OF.  
**40° C and + 80° C.**



## PE 100 REDUCER SDR 11 - PN 16



PART #	DIAMETER Ød	L	H1	H2	S1	S2
0329LRM02500150HP	75-50	130	56	58	6.8	4.5
0329LRM02500200HP	75-63	130	59	64	6.8	5.72
0329LRM03000150HP	90-50	138	63	52	8.18	4.5
0329LRM03000150HP	90-50	138	63	53	8.18	4.5
0329LRM03000200HP	90-63	138	63	60	8.18	5.72
0329LRM03000200HP	90-63	172	78	60	8.18	5.72
0329LRM03000250HP	90-75	172	78	60	8.18	6.8
0329LRM03000250HP	90-75	172	78	65	8.18	6.8
0329LRM04000150HP	110-50	172	78	65	10	4.54
0329LRM04000150HP	110-50	183	78	70	10	4.54
0329LRM04000200HP	110-63	183	78	68	10	5.72
0329LRM04000200HP	110-63	183	78	68	10	5.72
0329LRM04000250HP	110-75	183	78	72	10	6.8
0329LRM04000250HP	110-75	180	80	65	10	6.8
0329LRM04000300HP	110-90	180	80	70	10	8.18
0329LRM04000300HP	110-90	180	80	70	10	8.18
0329LRM04500300HP	125-90	180	80	75	11.36	8.18
0329LRM04500400HP	125-110	180	80	70	11.36	10
0329LRM06000200HP	160-63	203	85	67	14.54	5.72



PART #	DIAMETER Ød	L	H1	H2	S1	S2
0329LRTM06000250HP	160-75	208	85	75	14.54	6.8
0329LRTM06000300HP	160-90	214	85	83	14.54	8.18
0329LRTM06000400HP	160-110	214	85	83	14.54	10
0329LRTM06000450HP	160-125	214	85	85	14.54	11.36
0329LRTM07000400HP	180-110	170	85	80	16.36	10
0329LRTM07000450HP	180-125	170	85	80	16.36	11.36
0329LRTM08000200HP	200-63	218	100	67	11.76	5.72
0329LRTM08000250HP	200-75	218	100	75	11.76	6.8
0329LRTM08000300HP	200-90	218	100	93	11.76	8.18
0329LRTM08000400HP	200-110	218	100	97	11.76	10
0329LRTM08000600HP	200-160	210	100	100	11.76	14.54
0329LRTM08000700HP	200-180	210	100	108	11.76	16.36
0329LRTM09000400HP	225-110	218	80	87	20.45	10
0329LRTM08000600HP	225-160	218	80	80	20.45	14.54
0329LRTM09000800HP	225-200	218	80	90	20.45	18.18
0329LRTM10000400HP	250-110	260	90	100	22.72	10
0329LRTM10000600HP	250-160	230	90	93	22.72	14.54
0329LRTM10000800HP	250-200	230	90	97	22.72	18.18

PART #	DIAMETER Ød	L	H1	H2	S1	S2
0329LRTM10000900HP	250-225	230	90	100	22.72	20.45
0329LRTM11000400HP	280-110	255	105	95	25.45	10
0329LRTM11000400HP	280-160	245	105	105	25.45	14.54
0329LRTM11000700HP	280-180	245	105	105	25.45	16.36
0329LRTM11000800HP	280-200	245	105	120	25.45	18.18
0329LRTM11001000HP	280-250	245	105	130	25.45	22.72
0329LRTM12000400HP	315-110	235	90	87	28.63	10
0329LRTM12000600HP	315-160	235	90	85	28.63	14.54
0329LRTM12000800HP	315-200	240	90	90	28.63	18.18
0329LRTM12001000HP	315-250	240	90	100	28.63	22.72
0329LRTM14000400HP	355-110	270	105	100	32.27	10
0329LRTM14000600HP	355-160	275	105	110	32.27	14.54
0329LRTM14000800HP	355-200	260	105	110	32.27	18.18
0329LRTM14001000HP	355-250	240	105	110	32.27	22.72
0329LRTM16000900HP	400-200	270	100	110	36.36	18.18
0329LRTM16001000HP	400-250	250	100	110	36.36	22.72
0329LRTM16001200HP	400-315	230	100	110	36.36	28.63
0329LRTM18000800HP	450-200	270	105	100	40.90	18.18
0329LRTM18001000HP	450-250	270	105	110	40.90	22.72
0329LRTM18001200HP	450-315	250	105	110	40.90	28.63
0329LRTM18001600HP	450-400	245	105	120	40.90	36.36
0329LRTM20000800HP	500-200	280	98	105	45.45	18.18
0329LRTM20001000HP	500-250	280	98	110	45.45	22.72
0329LRTM20001200HP	500-315	275	98	110	45.45	28.63
0329LRTM20001600HP	500-400	275	98	120	45.45	36.36
0329LRTM20001800HP	500-450	275	98	120	45.45	40.90
0329LRTM22001200HP	560-315	280	105	110	50.90	28.63
0329LRTM22001600HP	560-400	260	105	120	50.90	36.36
0329LRTM22001800HP	560-450	250	105	120	50.90	40.90
0329LRTM22001200HP	630-315	285	110	100	57.27	28.63
0329LRTM22001600HP	630-400	285	110	120	57.27	36.36
0329LRTM22001800HP	630-450	275	110	120	57.27	40.90



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

[WWW.HYDROPLAST.PK](http://WWW.HYDROPLAST.PK)

**HDPE 100**  
**PE FITTINGS**