

HDPE 100

PE FITTINGS


POLYETHYLENE
Displays **GOOD**
CHEMICAL
RESISTANCE MATERIAL
STRENGTH AND RIGIDITY
WITHIN A TEMPERATURE
RANGE OF.
40° C and + 80° C.



PE 100

REDUCER

SDR 17 - PN 10



PART #	DIAMETER Ød	L	H1	H2	S1	S2
O329LRTM02500150HP	75-50	130	56	58	4.41	2.94
O329LRTM02500200HP	75-63	130	59	64	4.41	3.70
O329LRTM03000150HP	90-50	138	63	52	5.29	2.94
O329LRTM03000150HP	90-50	138	63	53	5.29	2.94
O329LRTM03000200HP	90-63	138	63	60	5.29	3.70
O329LRTM03000200HP	90-63	172	78	60	5.29	3.70
O329LRTM03000250HP	90-75	172	78	60	5.29	4.41
O329LRTM03000250HP	90-75	172	78	65	5.29	4.41
O329LRTM04000150HP	110-50	172	78	65	6.47	2.94
O329LRTM04000150HP	110-50	183	78	70	6.47	2.94
O329LRTM04000200HP	110-63	183	78	68	6.47	3.70
O329LRTM04000200HP	110-63	183	78	68	6.47	3.70
O329LRTM04000250HP	110-75	183	78	72	6.47	4.41
O329LRTM04000250HP	110-75	180	80	65	6.47	4.41
O329LRTM04000300HP	110-90	180	80	70	6.47	5.29
O329LRTM04000300HP	110-90	180	80	70	6.47	5.29
O329LRTM04500300HP	125-90	180	80	75	7.35	5.29
O329LRTM04500400HP	125-110	180	80	70	7.35	6.47
O329LRTM06000200HP	160-63	203	85	67	9.41	3.70



PART #	DIAMETER Ød	L	H1	H2	S1	S2
0329LRTM06000250HP	160-75	208	85	75	9.41	4.41
0329LRTM06000300HP	160-90	214	85	83	9.41	5.29
0329LRTM06000400HP	160-110	214	85	83	9.41	6.47
0329LRTM06000450HP	160-125	214	85	85	9.41	7.35
0329LRTM07000400HP	180-110	170	85	80	10.58	6.47
0329LRTM07000450HP	180-125	170	85	80	10.58	7.35
0329LRTM08000200HP	200-63	218	100	67	11.76	3.70
0329LRTM08000250HP	200-75	218	100	75	11.76	4.41
0329LRTM08000300HP	200-90	218	100	93	11.76	5.29
0329LRTM08000400HP	200-110	218	100	97	11.76	6.47
0329LRTM08000600HP	200-160	210	100	100	11.76	9.41
0329LRTM08000700HP	200-180	210	100	108	11.76	10.58
0329LRTM09000400HP	225-110	218	80	87	13.23	6.47
0329LRTM09000600HP	225-160	218	80	80	13.23	9.41
0329LRTM09000800HP	225-200	218	80	90	13.23	11.76
0329LRTM10000400HP	250-110	260	90	100	14.70	6.47
0329LRTM10000600HP	250-160	230	90	93	14.70	9.41
0329LRTM10000800HP	250-200	230	90	97	14.70	11.76

PART #	DIAMETER Ød	L	H1	H2	S1	S2
0329LRTM10000900HP	250-225	230	90	100	14.70	13.23
0329LRTM11000400HP	280-110	255	105	95	16.47	6.47
0329LRTM11000600HP	280-160	245	105	105	16.47	9.41
0329LRTM11000700HP	280-180	245	105	105	16.47	10.58
0329LRTM11000800HP	280-200	245	105	120	16.47	11.76
0329LRTM11001000HP	280-250	245	105	130	16.47	14.70
0329LRTM12000400HP	315-110	235	90	87	18.52	6.47
0329LRTM12000600HP	315-160	235	90	85	18.52	9.41
0329LRTM12000800HP	315-200	240	90	90	18.52	11.76
0329LRTM12001000HP	315-250	240	90	100	18.52	14.70
0329LRTM14000400HP	355-110	270	105	100	20.88	6.47
0329LRTM14000600HP	355-160	275	105	110	20.88	9.41
0329LRTM14000800HP	355-200	260	105	110	20.88	11.76
0329LRTM14001000HP	355-250	240	105	110	20.88	14.70
0329LRTM16000800HP	400-200	270	100	110	23.52	11.76
0329LRTM16001000HP	400-250	250	100	110	23.52	14.70
0329LRTM16001200HP	400-315	230	100	110	23.52	18.52
0329LRTM18000800HP	450-200	270	105	100	26.47	11.76
0329LRTM18001000HP	450-250	270	105	110	26.47	14.70
0329LRTM18001200HP	450-315	250	105	110	26.47	18.52
0329LRTM18001600HP	450-400	245	105	120	26.47	23.52
0329LRTM20000800HP	500-200	280	98	105	29.41	11.76
0329LRTM20001000HP	500-250	280	98	110	29.41	14.70
0329LRTM20001200HP	500-315	275	98	110	29.41	18.52
0329LRTM20001600HP	500-400	275	98	120	29.41	23.52
0329LRTM20001800HP	500-450	275	98	120	29.41	26.47
0329LRTM22001200HP	560-315	280	105	110	32.94	18.52
0329LRTM22001600HP	560-400	260	105	120	32.94	23.52
0329LRTM22001800HP	560-450	250	105	120	32.94	26.47
0329LRTM24001200HP	630-315	285	110	100	37.05	18.52
0329LRTM24001600HP	630-400	285	110	120	37.05	23.52
0329LRTM24001800HP	630-450	275	110	120	37.05	26.47



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS