

# HDPE 100


## PE FITTINGS

**POLYETHYLENE**  
Displays **GOOD**  
**CHEMICAL**  
**RESISTANCE MATERIAL**  
**STRENGTH AND RIGIDITY**  
WITHIN A TEMPERATURE  
RANGE OF.  
**40° C and + 80° C.**



**PE 100**

# REDUCING TEE

**SDR 11 - PN 16**


PART #	DIAMETER Ød	L	L1	L2	H	S1	S
O329LRTM02500150HP	75-50	199	70	55	94	6.81	4.54
O329LRTM03000150HP	90-50	243	80	65	115	8.18	4.54
O329LRTM02500200HP	90-63	243	80	68	123	8.18	5.72
O329LRTM02500250HP	90-75	270	80	75	130	8.18	6.81
O329LRTM04000150HP	110-50	242	83	60	125	10	4.54
O329LRTM04000200HP	110-63	242	83	62	130	10	5.72
O329LRTM04000250HP	110-75	275	83	80	138	10	6.81
O329LRTM04000300HP	110-90	275	83	82	140	10	8.18
O329LRTM04500300HP	125-90	305	80	75	150	11.36	8.18
O329LRTM04500400HP	125-110	305	80	75	150	11.36	10
O329LRTM05000300HP	140-90	253	75	75	155	8.23	8.18
O329LRTM05000400HP	140-110	253	70	80	160	8.23	10
O329LRTM06000200HP	160-63	333	100	80	175	14.54	5.72
O329LRTM06000250HP	160-75	333	100	80	175	14.54	6.81
O329LRTM06000300HP	160-90	333	100	80	175	14.54	8.18
O329LRTM06000400HP	160-110	333	100	80	175	14.54	10
O329LRTM06000450HP	160-125	380	98	100	190	14.54	11.36
O329LRTM07000300HP	180-90	270	85	80	180	16.36	8.18
O329LRTM07000400HP	180-110	270	85	85	185	16.36	10
O329LRTM07000450HP	180-125	400	90	85	185	16.36	11.36
O329LRTM08000200HP	200-63	338	95	75	195	18.18	5.72
O329LRTM08000250HP	200-75	338	95	80	195	18.18	6.81
O329LRTM08000300HP	200-90	338	95	85	195	18.18	8.18

PART #	DIAMETER Ød	L	L1	L2	H	S1	S2
0329LRTM08000400HP	200-110	338	95	85	195	18.18	10
0329LRTM08000600HP	200-160	368	95	85	200	18.18	14.54
0329LRTM09000300HP	225-90	285	90	75	200	20.45	8.18
0329LRTM09000400HP	225-110	285	85	75	200	20.45	10
0329LRTM09000600HP	225-160	335	85	75	200	20.45	14.54
0329LRTM09000700HP	225-180	400	85	75	200	20.45	16.36
0329LRTM10000200HP	250-63	365	110	85	235	22.72	5.72
0329LRTM10000250HP	250-75	365	110	90	235	22.72	6.81
0329LRTM10000300HP	250-90	365	110	100	245	22.72	8.18
0329LRTM10000400HP	250-110	365	110	110	245	22.72	10
0329LRTM10000600HP	250-160	505	110	110	250	22.72	14.54
0329LRTM10000800HP	250-200	505	110	110	250	22.72	18.18
0329LRTM11000400HP	280-110	300	100	100	240	25.45	10
0329LRTM11000600HP	280-160	387	100	100	250	25.45	14.54
0329LRTM11000800HP	280-200	387	100	105	250	25.45	18.18
0329LRTM12000200HP	315-63	370	110	90	270	28.63	5.72
0329LRTM12000250HP	315-75	370	110	90	270	28.63	6.81
0329LRTM12000300HP	315-90	370	110	100	280	28.63	8.18
0329LRTM12000400HP	315-110	370	110	110	280	28.63	10
0329LRTM12000600HP	315-160	460	110	110	285	28.63	14.5
0329LRTM12000800HP	315-200	460	110	110	285	28.63	18.18
0329LRTM12001000HP	315-250	575	103	110	285	28.63	22.72
0329LRTM12000800HP	355-90	330	110	100	287	32.27	8.18
0329LRTM14000400HP	355-110	350	110	100	287	32.27	10
0329LRTM14000600HP	355-160	400	110	100	287	32.27	14.5
0329LRTM14000800HP	355-200	440	110	100	287	32.27	18.18
0329LRTM14001000HP	355-250	490	110	100	287	32.27	22.72
0329LRTM14001200HP	355-315	555	110	100	287	30.27	28.63
0329LRTM16000300HP	400-90	340	110	100	310	36.36	8.18
0329LRTM16000400HP	400-110	360	110	100	310	36.36	10
0329LRTM16000600HP	400-160	400	110	100	310	36.36	14.5
0329LRTM16000800HP	400-200	450	110	100	310	36.36	18.18
0329LRTM16001000HP	400-250	490	110	100	310	36.36	22.72
0329LRTM16001200HP	400-315	555	110	100	310	36.36	28.63



PART #	DIAMETER Ød	L	L1	L2	H	S1	S2
O329LRTM16001400HP	400-355	595	110	100	310	36.36	32.27
O329LRTM18000400HP	450-110	375	120	120	365	40.90	10
O329LRTM18000450HP	450-125	464	150	120	365	40.90	10.90
O329LRTM18000600HP	450-160	464	130	120	365	40.90	14.54
O329LRTM18000800HP	450-200	464	120	120	365	40.90	18.18
O329LRTM18000900HP	450-225	545	150	130	375	40.90	20.45
O329LRTM18001000HP	450-250	545	140	130	375	40.90	22.72
O329LRTM18001100HP	450-280	600	140	140	385	40.90	25.45
O329LRTM18001200HP	450-315	600	130	140	385	40.90	28.63
O329LRTM18000600HP	450-355	660	140	160	405	40.90	32.27
O329LRTM18001600HP	450-400	670	120	160	405	40.90	36.36
O329LRTM20000400HP	500-110	398	130	135	420	45.45	10
O329LRTM20000600HP	500-160	495	140	135	420	45.45	14.54
O329LRTM20000900HP	500-225	545	150	135	420	45.45	20.45
O329LRTM20001200HP	500-315	635	145	145	430	45.45	28.63
O329LRTM22000400HP	560-110	410	135	140	445	50.90	10
O329LRTM22000600HP	560-160	450	135	140	445	50.90	14.54
O329LRTM22000800HP	560-200	508	135	140	445	50.90	18.18
O329LRTM22001000HP	560-250	545	135	140	445	50.90	22.72
O329LRTM22001200HP	560-315	605	135	145	450	50.90	28.63
O329LRTM22001600HP	560-400	720	135	160	465	50.90	36.36
O329LRTM24000400HP	630-110	475	145	135	480	57.27	10

PART #	DIAMETER Ød	L	L1	L2	H	S1	S2
O329LRTM24000600HP	630-160	475	140	140	485	57.27	14.54
O329LRTM24000800HP	630-200	550	150	145	490	57.27	18.18
O329LRTM24001000HP	630-250	555	140	145	490	57.27	22.72
O329LRTM24001200HP	630-315	665	150	145	490	57.27	28.63
O329LRTM24001600HP	630-400	725	145	160	505	57.27	36.36
O329LRTM24001800HP	630-450	800	150	180	525	57.27	40.90





 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

[WWW.HYDROPLAST.PK](http://WWW.HYDROPLAST.PK)

**HDPE 100**  
**PE FITTINGS**