


HDPE 100

PE FITTINGS

POLYETHYLENE
Displays **GOOD**
CHEMICAL
RESISTANCE MATERIAL
STRENGTH AND RIGIDITY
WITHIN A TEMPERATURE
RANGE OF.
40° C and + 80° C.



PE 100
TRANSITION ADAPTOR
**SDR 11 PE BRASS MALE THREAD
WATER 16 BAR INJECTED -SPIGOT**


PART #	DIAMETER Ød	Z	Le	S	WEIGHT(KG)
O329NTAM0050HP	20	90	41	3.0	0.084
O329NTAM0075HP	25	84	41	3.0	0.104
O329NTAM0100HP	32	103	44	3.0	0.208
O329NTAM0125HP	40	122	49	3.7	0.310
O329NTAM0150HP	50	121	55	4.6	0.398
O329NTAM0200HP	63	140	63	5.8	0.578
O329NTAM0250HP	75	146	70	6.8	0.982
O329NTAM0300HP	90	168	79	8.2	1.380
O329NTAM0400HP	110	179	82	10.0	2.030
O329NTAM0450HP	125	186	87	11.4	2.226



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS