

HDPE 100

PE FITTINGS


POLYETHYLENE
Displays **GOOD**
CHEMICAL
RESISTANCE MATERIAL
STRENGTH AND RIGIDITY
WITHIN A TEMPERATURE
RANGE OF.
40° C and + 80° C.



PE 100

TRANSITION ADAPTOR

SDR 11 PE BRASS MS-58 FEMALE THREAD
WATER 16 BAR INJECTED -SPIGOT



PART #	DIAMETER Ød	Z	Le	S	WEIGHT(KG)
0329NTAF0050HP	20	72	41	3.0	0.058
0329NTAF0075HP	25	72	41	3.0	0.072
0329NTAF0100HP	32	84	44	3.0	0.152
0329NTAF0125HP	40	98	49	3.7	0.318
0329NTAF0150HP	50	101	55	4.6	0.304
0329NTAF0200HP	63	115	63	5.8	0.386
0329NTAF0250HP	75	129	70	6.8	0.828
0329NTAF0300HP	90	144	79	8.2	1.122
0329NTAF0400HP	110	147	82	10.0	1.732
0329NTAF0450HP	125	153	87	11.4	1.806



 /hydroplast-fittings

 hydroplast

 /hydroplast

 info@hydroplast.pk

WWW.HYDROPLAST.PK

HDPE 100
PE FITTINGS